

Specification Sheet

BWC Part Number#: 4060

Description: 14 AWG 2 conductor 19 strands bare copper wire with PVC insulation, unshielded, with an

overall plenum rated PVC jacket.

1. Conductor

1.1. AWG Size & Stranding: 14 AWG 19 Strands Class C 1.2. Material: Annealed Bare Copper

1.3. Conductor Count: 2 Conductors

2. Insulation

2.1. Material: Polyvinylchloride

2.2. Wall Thickness: 0.009"

2.3. Diameter: 0.091" ± 0.002" 2.4. Color Code: Black, White

3. Cable Assembly

3.1. Lay Length:

4.00" LHL (3.0 tw/ft), Nominal

4. Jacket

4.1. Material:

4.2. Wall Thickness:

4.3. Diameter:

4.4. Color:

4.5. Ripcord:

4.6. Weight:

Polyvinylchloride

0.015"

0.213" ± 0.020"

Natural

Yes

37 Lbs/Mft

5. Markings

5.1. Type: Cable permanently identified via surface inkjet print 5.2. Legend: LAKE CABLE E171202 14AWG 2C 75°C (UL) FT-6 "ROHS"

COMPLIANT" MADE IN USA

5.3. Footage Markers: Yes

6. Standards

6.1. Cable suitable for installation under NEC (NFPA 70) articles 725 and 760 guidelines

6.2. Cable meets NFPA 262 (Steiner tunnel) flame test

6.3. Cable meets RoHS 2002/95/EC Directive, RoHS 2 2011/65/EU Directive, RoHS 3 2015/863/EU Directive

6.4. Cable is REACH compliant per Regulation (EC) No 1907/2006 (211) Updated January 19, 2021

6.5. Made in the USA

6.6. WARNING: This product may contain chemicals, such as Vinyl Chloride, known to the state of California to cause cancer. For more information, go to www.P65Warnings.ca.gov. Wash hands after handling

ALL SPECIFIED PARAMETERS WITHOUT A TOLERANCE ARE NOMINAL AND SUBJECT TO VERIFICATION. BEST WIRE IS NOT RESPONSIBLE FOR UNKNOWN PERFORMANCE ATTRIBUTES THAT WERE NOT MADE KNOWN TO BEST WIRE AT THE TIME OF DESIGN.



