



## Specification Sheet

**BWC Part Number #: WN-4050-65-DB**

### Physical Characteristics

Conductor	Oxygen Free B.C.
Number of Conductor	2
AWG	16
Stranding	65
Diameter	0.0063 (inches)
Insulation Material	PVC
Diameter	0.0827 (inches)
Nominal Wall	0.0098 (inches)
Jacket Material	FR-PVC
Overall Diameter	0.2008 (inches)
Nominal Thickness	0.0197 (inches)
Paper Tape	YES
Rip Cord	YES
Conductor Resistance	15.8 (ohms)
Nominal Weight	16 (pounds)
Voltage Rating	300V (volts)
Temperature Rating	-20C – 70C

### Description

- 16/2 Stranded CMR/CL3R Direct Burial Sound Audio Cable

### Applicable Standards

- For Communication and Signal Control Systems
- 2 Oxygen Free Bare Copper Conductors in an Overall Jacket

### Colors

- Insulation Color: Black / Red
- Jacket Color: Black

### Cable Marking

AUDIO CABLE 2 COND 16AWG HI-STRAND OFC CMR/CL3R DIRECT BURIAL AUDIO CABLE SUN RES EXXXXXX C(ETL)US \*\*\*FT



**ALL SPECIFIED PARAMETERS WITHOUT A TOLERANCE ARE NOMINAL AND SUBJECT TO VERIFICATION. BEST WIRE IS NOT RESPONSIBLE FOR UNKNOWN PERFORMANCE ATTRIBUTES THAT WERE NOT MADE KNOWN TO BEST WIRE AT THE TIME OF DESIGN.**

**GET WIRED**

1343 Exchange Dr. Richardson, TX 75081 | 972-231-5600 | [www.bestwirecable.com](http://www.bestwirecable.com)

Information on this specification is subject to change without notice. REV 03062023

