



Specification Sheet

BWC Part Number #: WN-4050-65

Description

- 16/2 Stranded CMR/CL3R Sound Audio Cable

Applicable Standards

- For Communication and Signal Control Systems
- 2 Oxygen Free Bare Copper Conductors in an Overall Jacket

Colors

- Insulation Color: Black / Red
- Jacket Color: Black, White

Cable Marking

AUDIO CABLE 2 COND 16AWG HI-STRAND OFC CMR/CL3R FT4 75C
EXXXXXX C(ETL)US ***FT



Physical Characteristics

Conductor	Oxygen Free B.C.
Number of Conductor	2
AWG	16
Stranding	65
Diameter	0.0063 (inches)
Insulation Material	PVC
Diameter	0.0827 (inches)
Average Thickness	0.0122 (inches)
Min. Point Thickness	0.0106 (inches)
Assembly Diameter	0.1614 (inches)
Jacket Material	PVC
Outer Diameter	0.2008 (inches)
Average Thickness	0.0197 (inches)
Min. Point Thickness	0.0177 (inches)
Rip Cord	Nylon
Conductor Resistance	15.5 (ohms)
Nominal Weight	15 (pounds)
Voltage Rating	300V (volts)

ALL SPECIFIED PARAMETERS WITHOUT A TOLERANCE ARE NOMINAL AND SUBJECT TO VERIFICATION. BEST WIRE IS NOT RESPONSIBLE FOR UNKNOWN PERFORMANCE ATTRIBUTES THAT WERE NOT MADE KNOWN TO BEST WIRE AT THE TIME OF DESIGN.

GET WIRED

1343 Exchange Dr. Richardson, TX 75081 | 972-231-5600 | www.bestwirecable.com

Information on this specification is subject to change without notice. REV 03062023



SCAN ME