



Specification Sheet

BWC Part Number #: WN-4250-65-DB

Physical Characteristics

Conductor	Oxygen Free B.C.
Number of Conductor	4
AWG	16
Stranding	65
Diameter	0.0063 (inches)
Insulation Material	PVC
Diameter	0.0827 (inches)
Nominal Wall	0.0098 (inches)
Jacket Material	FR-PVC
Overall Diameter	0.2559 (inches)
Nominal Thickness	0.02165 (inches)
Paper Tape	YES
Rip Cord	YES
Conductor Resistance	15.8 (ohms)
Nominal Weight	28 (pounds)
Voltage Rating	300V (volts)

Description

- 16/4 Stranded CMR/CL3R Direct Burial Sound Audio Cable

Applicable Standards

- For Communication and Signal Control Systems
- 4 Oxygen Free Bare Copper Conductors in an Overall Jacket

Colors

- Insulation Color: Black / Red / White / Green
- Jacket Color: Black

Cable Marking

AUDIO CABLE 4 COND 16AWG HI-STRAND OFC CMR/CL3R DIRECT BURIAL AUDIO CABLE SUN RES EXXXXXX C(ETL)US ***FT



ALL SPECIFIED PARAMETERS WITHOUT A TOLERANCE ARE NOMINAL AND SUBJECT TO VERIFICATION. BEST WIRE IS NOT RESPONSIBLE FOR UNKNOWN PERFORMANCE ATTRIBUTES THAT WERE NOT MADE KNOWN TO BEST WIRE AT THE TIME OF DESIGN.

GET WIRED

1343 Exchange Dr. Richardson, TX 75081 | 972-231-5600 | www.bestwirecable.com

Information on this specification is subject to change without notice. REV 03062023

